

- Ozone dissolving system for water electrolysis in electronic components cleaning facility - has gas dissolution membrane module row formed by connecting water flow lines and gas flow paths of adjacent dissolution membrane modules, **water** and **gas flow** in counter- current direction.

L20 ANSWER 83 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 1999-586229 [50] WPINDEX

DNC C1999-171279

DC D15 E36 J03

PA (KURK) KURITA WATER IND LTD

CYC 1

PI JP 11256193 A 19990921 (199950)* 6p

ADT JP 11256193 A JP 1998-63426 19980313

PRAI JP 1998-63426 19980313

AN 1999-586229 [50] WPINDEX

AB JP 11256193 A UPAB: 19991201

NOVELTY - The gas dissolution membrane module row is formed by connecting the water flow lines and gas flow paths of adjacent gas dissolution membrane modules in series. At one end of the gas dissolution membrane module row, there is an inlet for ozone content gas (7) in the gas flow line and outlet for ozone-treated water (8) in water line.

DETAILED DESCRIPTION - At the other end of the membrane module row there is an exhaust outlet of ozone (9) in gas flow line and inlet opening of raw water (10) on water **flow** line. The **gas** and **water flow** in counter-current direction.

USE - For dissolving ozone in water which is used for cleaning electronic components.

ADVANTAGE - By using the gas dissolution membrane module, ozone dissolved water, of fixed concentration is obtained. The rate of dissolution of ozone is increased.

DESCRIPTION OF DRAWING - The figure shows the ozone dissolving unit.
(7) Inlet for ozone containing gas; ; (8) Outlet for ozone-treated water;
; (9) Exhaust outlet of ozone; ; (10) Raw water.
Dwg.1/3